



----- CHASSIS -----

CHASSIS: KME EXCEL XMPD 10" RR  
 CAB: 4 DOOR CUMMINS ISM 500 HP  
 TRANSMISSION: ALLISON 4000EVS  
 FRONT AXLE: 20,000#  
 REAR AXLE: 31,000#

----- PUMP -----

PUMP: HAILE QMAX-150 1500 GPM SINGLE STAGE  
 INTAKES  
 DRIVER SIDE: 6" & 2 1/2"  
 OFFICER SIDE: 6" & 2 1/2"  
 FRONT:  
 REAR:

DISCHARGES  
 DRIVER SIDE: (2) 2 1/2" & (1) 4"  
 OFFICER SIDE: (1) 2 1/2" & (1) 4"  
 FRONT:  
 REAR: (1) 2 1/2"  
 DECK GUN:  
 OTHER: (2) 1 3/4" CROSSSLAYS  
 (1) 3" CROSSSLAY

----- TANK -----

TANK: UPF POLY IIR  
 WATER: 1,500  
 FOAM:  
 EXTRA FILLS: (2) 2 1/2" BETTS  
 DUMPS: (2) NEWTONS

----- BODY -----

BODY TYPE: 163" PLATBACK  
 MATERIAL: 3/16" ALUMINUM  
 COMPARTMENTATION  
 DRIVER SIDE: LOW W/AIR PACK  
 OFFICER SIDE: 3/4" HEIGHT-SPLIT DEPTH  
 HOSEBED  
 CAPACITY: 80 CU. FT.  
 DIVIDERS: THREE (3)  
 HOSE LOAD: 1,000' OF 5"

----- MISC. -----

GENERATOR: SMART POWER TM-20 20,000W HYD  
 FOAM SYSTEM:

CUSTOMER APPROVAL:

NAME: \_\_\_\_\_  
 TITLE: \_\_\_\_\_  
 DATE: \_\_\_\_\_

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT  
 NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS.  
 CONTRACT SPECIFICATIONS SHALL PREVAIL OVER DRAWING.

SY#	DATE	REVISION DESCRIPTION	APP'D
A	5-26-06	REVISED	JGM

SALES ENGINEER : JASON WITTMER



KOVATCH MOBILE EQUIPMENT  
 ONE INDUSTRIAL COMPLEX - NESQUEHONING, PA 18240

DATE: 4-25-06 SCALE: 1"=24" DWG SIZE: DRAWN BY: JJM APPROVED BY: JGM

KME CUSTOM PUMPER

MANCHESTER, MD

GSO#6600