

SPECIFICATIONS

CHASSIS: PANTHER LPD 12" RR
 ENGINE: CUMMINS ISL 425 HP
 TRANSMISSION: ALLISON 3000EVS, 5-SPEED AUTOMATIC
 FRONT AXLE: MERRITOR 21,480 lbs.
 REAR AXLE: MERRITOR 31,000 lbs.
 RESCUE BODY: 17'-10" WALK AROUND ALUMINUM

COMPARTMENT SIZE

L1/R1: 68"H x 55 1/4"W x 29"D / TRANSVERSE
 L2/R2: 68"H x 54 1/8"W x 29"D / TRANSVERSE
 L3/R3: 36"H x 57 1/2"W x 29"D
 L4/R4: 68"H x 45 1/4"W x 29"D
 REAR: 68"H x 42"W x 40"D/29"D

DOOR OPENING

L1/R1: 64"H x 52"W
 L2/R2: 64"H x 52"W
 L3/R3: 32"H x 53"W
 L4/R4: 64"H x 42"W
 REAR: 64"H x 42"W

MISC.

PUMP: HALE CBP250 PTO
 SUCTIONS:
 (1) 3" NST DRIVER SIDE
 (1) 2 1/2" NST AUX. DRIVER SIDE
 DISCHARGES:
 (1) 2 1/2" NST DRIVER SIDE
 (1) 1-1/2" NST CROSSLAY
 WATER TANK: 300 GALLON UPF POLY
 FOAM TANK: 30 GALLON UPF POLY
 GENERATOR: HARRISON 15MPC HYDRAULIC 15kW
 WHEEL LED WARNING LIGHT PACKAGE

CUSTOMER PAINT CODES

LOWER CAB AND BODY: RED PRG# FTB002030
 CAB TWO TONE (IF APPLICABLE): N/A
 COMPARTMENT INTERIOR: ZOLATONE #20-63

**PLEASE REVIEW AND RETURN
 A SIGNED COPY.**

NAME:
 TITLE:
 DATE:

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT
 NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS



C	03MAR09	REV. PER SHELVING UPDATE	JBB
B	07JAN09	REV. PER BODY RELEASE	JBB
A	17DEC08	REV. PER PRE-CONSTRUCTION	JBB
SYM	DATE	REVISION DESCRIPTION	APP'D

KOVATCH MOBILE EQUIPMENT
 ONE INDUSTRIAL COMPLEX
 NESQUEHANNING, PA 15240

TOLERANCE UNLESS OTHERWISE SPECIFIED
 DECIMALS: .0005
 ONE PLACE: ± .0005
 TWO PLACE: ± .001
 THREE PLACE: ± .0005
 FRACTIONS: ± 1/8"
 REMOVE ALL SHARP
 AND SHARP EDGES

SCALE: NONE
 DRAWN BY: JBB
 APPROVED BY: JBB

KME HEAVY DUTY RESCUE
 SCRANTON, PA
 GSO #7475

DO NOT CHANGE MANUALLY

