



SPECIFICATIONS

CHASSIS: INTL 7600 2 DOOR
 ENGINE: NAVISTAR 350HP
 TRANSMISSION: ALLISON 3000EVS
 FRONT AXLE: 14,000LB
 REAR AXLE: 26,000LB
 RESCUE BODY: 3-COMP^T WALK AROUND RESCUE

COMPARTMENT SIZE

(L1/R1): 76"H X 57 1/4"W X 29"D/TRANSVERSE
 (L2/R2): 54"H X 64 1/2"W X TRANSVERSE
 (L3/R3): 76"H X 52 1/8"W X 29"D/TRANSVERSE
 (REAR): 68"H X 62"W X 28"D

DOOR OPENING

(L1/R1): 72"H X 54"W
 (L2/R2): 42"H X 60"W
 (L3/R3): 72"H X 50"W
 (REAR): 64"H X 62"W

**PLEASE REVIEW AND RETURN
 A SIGNED COPY.**

NAME: _____
 TITLE: _____
 DATE: _____

CUSTOMER PAINT CODES:

LOWER CAB/BODY: PPG RED#Z4844
 CAB TWO TONE: PPG WHITE #8000
 COMPARTMENT INTERIOR: _____

THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT
 NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS



F	5-28-10	REVISED	AY
E	3-16-10	REVISED	AY
D	1-8-09	REVISED	AY
C	12-10-09	REVISED	AY
B	11-10-09	REVISED	AY
A	9-16-09	REVISED	AY
SYM	DATE	REVISION DESCRIPTION	APP'D

SALES ENGINEER: ANDREW YENSER

KOVATCH MOBILE EQUIPMENT
 ONE INDUSTRIAL COMPLEX
 NESQUEHANNING, PA 186240

TOLERANCE UNLESS OTHERWISE SPECIFIED
 DECIMALS
 ONE PLACE: ±.060 THREE PLACE: ±.000 FRACTIONS: ±1/8"
 TWO PLACE: ±.030 ANGLES: ±2°
 REMOVE ALL BORES AND SHARP EDGES

CAD

KME AIR/LIGHT RESCUE

GLADWYNE, PA

GS0#7848

DO NOT CHANGE MANUALLY