



SPECIFICATIONS

CHASSIS: 2008 FORD F750 4X2 2 DOOR
 ENGINE: CAT C7 300 HP
 TRANSMISSION: ALLISON 3000 EVS, 5-SPEED
 FRONT AXLE: 12,000 lbs.
 REAR AXLE: 23,000 lbs.
 RESCUE BODY: 4 COMPT W.A. ALUMINUM

COMPARTMENT SIZE

(L1/R1): 80"H X 39 1/4"W X 26"D / TRANSVERSE
 (L2/R2): 80"H X 38 1/8"W X 26"D / TRANSVERSE
 (L3/R3): 48"H X 57 1/2"W X TRANSVERSE
 (L4/R4): 80"H X 47 1/4"W X 26"D
 (REAR): 64"H X 44"W X 50"D

DOOR OPENING

(L1/R1): 64"H X 36"W
 (L2/R2): 64"H X 36"W
 (L3/R3): 32"H X 52"W
 (L4/R4): 64"H X 46"W
 (REAR): 59"H X 44"W

**PLEASE REVIEW AND RETURN
 A SIGNED COPY.**

NAME: _____

TITLE: _____

DATE: _____

CUSTOMER PAINT CODES:

LOWER CAB AND BODY: _____

CAB TWO TONE (IF APPLICABLE): _____

**THIS DRAWING IS A GENERAL CONFIGURATION AND MAY NOT
 NECESSARILY REFLECT ALL CONTRACTUAL REQUIREMENTS**

WINCO #25,000 WATT PTO GENERATOR



A				
SYM	DATE	REVISION	DESCRIPTION	APP'D

KOVATCH MOBILE EQUIPMENT
 ONE INDUSTRIAL COMPLEX
 NESQUEHONING, PA 18240

TOLERANCE UNLESS OTHERWISE SPECIFIED
 DECIMALS FRACTIONS: ±1/8"
 ONE PLACE: ± .060 THREE PLACE: ±.010 REMOVE ALL BURRS
 TWO PLACE: ± .030 ANGLES: ±2° AND SHARP EDGES

DATE SCALE DRAWN BY **JJM**
 2-18-10 NONE APPROVED BY

KME COMMERCIAL RESCUE

STOCK UNIT

GSO#7980

CAD

DO NOT CHANGE MANUALLY